



Thermafiber- Technical Bulletin

Thermafiber® FIRESpan™ / FIRESpan™ 90 Insulation

Thermafiber FIRESpan / FIRESpan 90 Insulation is an Underwriter Laboratory (UL) and Intertek/Omega Point Laboratory (OPL) listed and labeled product. FIRESpan / FIRESpan 90 and FIRESpan SS / FIRESpan 40 are the only Thermafiber brand curtain wall insulations approved for use in the perimeter fire containment systems tested and rated by these laboratories.* FIRESpan / FIRESpan 90 has a nominal density of 8 pcf (pounds per cubic foot).

Thermafiber® FIRESpan™ SS / FIRESpan™ 40 Insulation

Thermafiber FIRESpan SS / FIRESpan 40 Insulation is an Underwriter Laboratory (UL) and Intertek/Omega Point Laboratory (OPL) listed and labeled product. FIRESpan / FIRESpan 90 and FIRESpan SS / FIRESpan 40 are the only Thermafiber brand curtain wall insulations approved for use in the perimeter fire containment systems tested and rated by these laboratories.* FIRESpan SS / FIRESpan 40 has a density of 4 pcf (pounds per cubic foot).

For more information regarding FIRESpan / FIRESpan 90 and/or FIRESpan SS / FIRESpan 40 Insulation, please refer to Thermafiber literature TF686 or visit our website at www.thermafiber.com.

** Refer to specific tested assembly to determine whether FIRESpan / FIRESpan 90 or FIRESpan SS / FIRESpan 40 is to be installed in the perimeter fire containment system.*